

LIVING

CARATTERISTICHE TECNICHE

Motore	Brose Drive-S 36 Volt, Max power: 250 Watt, Torque/Coppia: 90 Nm
Batteria	Fantic Integra, Lithium Ion, 36 Volt, 630Wh
Display	Brose-Marquardt multifunctional display & push-assistance selection unit
Telaio	Aluminium frame. Sizes: S - M - L
Forcella	SR SUNTOUR XCR34 29" - 100mm
Cambio	SRAM GX 10-gear
Guarnitura	Miche 38t Aluminium
Protezione motore	Motor flange integrated in the frame for full motor protection
Pignoni	SRAM PG 1030 10-gear 11-36 teeth
Catena	KMC e-bike edition
Freno ant.	SRAM Level hydraulic, 180mm disc
Freno post.	SRAM Level hydraulic, 160mm disc
Pneumatici	Schwalbe Super Moto da 27,5" X 2.8
Cerchi e raggi	Aluminium alloy, stainless steel spokes
Mozzo ant.	110mm trough axle 15mm
Mozzo post.	148mm trough axle 12mm
Manubrio	Fantic alloy: rise 700mm
Attacco manubrio	Fantic 80mm
Serie sterzo	FSA No. 57 Orbit semi-integrated 1.5" - 1" 1/8
Sella	Sporturer Talisman Gelflow
Manopole	Fantic
Pedali	NVL 87b in aluminium